HARDIN MARINE


11 Industry Dr. Palm Coast, FL 32137 386-445-2500 / FAX 386-445-1122

PART NO.

755-843X

TITLE:

2PC VALVE COVER-INSTALLATION



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	100-720-1120	HOSE CLAMP	2
2	620-70153	BREATHER, 1-1/2	2
3	625-1029	O-RING	4
4	625-1282	O-RING 2PC VALVE COVER	2
5	625-1920	O-RINGS	4
6	755-8401	CAP, 2 PC VALVE COVER	2
7	755-8402	STUD, KE VC	4
8	755-8403	KNOB, 2PC VALVE COVER	4
9	755-8404	BREATHER, EXTENSION 2PC V/C	2
10	755-8407	RAIL, RECEIVER	2
11	755-8410	VALVE COVER, KE 2 PC	2
12	90025C02LHB	BOLT, 1/4-20x5/8	14
13	90031AN-TNSS	WASHER, 5/16 AN	4
14	90031PS-STSS	WASHER, 5/16 SEALING	4


KIT COMES IN PAIRS TO DO 1 ENGINE!

INSTALLATION INSTRUCTIONS

- 1) IF YOU PURCHASED 755-8430 PLAIN SET YOU WILL NEED TO ASSEMBLE THE VALVE COVERS.
- 2) SLIDE #13 WASHERS OVER #7 STUDS.
- 3) SIDE STUDS INTO VALVE COVERS. INSTALL #14 WASHER. APPLY GREEN LOCTITE AND INSTALL #8 NUT. TO TIGHTEN DOUBLE NUT THE BOTTOM OF THE STUD WITH 3/8-16 JAM NUTS.
- 4) MOUNT #10 RAIL TO THE HEAD USING #12 BOLTS. WE RECOMEND USING 755-8421 HIPPERFORMANCE SILICONE GASKETS. USING 1/8 HEX SOCKET TORQUE TO 120/130 INCH LBS...
- 5) OIL #4 O-RING AND INSTALL INTO THE GROOVE IN THE VALVE COVER.
- 6) USING THE THUMB SCREWS, TIGHTEN VALVE COVER TILL IT JUST TOUCHES THE RECEIVER RAIL. NOW PUSH DOWN ON THE INSTAKE SIDE OF THE COVER. TIGHTEN SCREWS A FEW TURNS AND PUSH ON THE INTAKE SIDE AGAIN. CONTINUE SLOWLY TIGHTEN THE SCREWS AND PUSHING DOWN ON THE INTAKE SIDE TILL THE VALVE COVER IS SEATED AGAINIST THE RECEIVER RAIL. USING 1/2 SOCKET TORQUE TO 20-25 FT. LBS...

7) INSTALL OIL CAP AND BREATHERS. THESE VALVE COVERS ARE MACHINED TO -20 AN. THE INSIDE OF #9 BREATHER EXTENSION IN ALL MACHINED FOR 1" NPT THREADS.

1.98



THIS DRAWING IS CONFIDENTIAL AND IS SUPPLIED ON EXPRESS CONDITION THAT IT SHALL NOT BE LENT, COPIED OR DISCLOSED TO ANY OTHER PERSON OR USED FOR ANY OTHER PURPOSE WITHOUT WRITTEN CONSENT OF HARDIN MARINE INC.. BREACH OF THIS CONTRACT WILL HOLD AND IT'S PRINCIPALS LIABLE FOR LOSS AND DAMAGES.